

AMENDMENTS TO THE CLAIMS

1. (previously presented) A correction tape dispenser comprising:
a tape comprising a carrier ribbon with correction composition thereon[.];
supply and take-up spools for the tape[.]; and,
a tip having an edge for pressing the tape against a surface, a portion of the tape
between the supply and take-up spools being guided to extend around said edge, wherein the
edge is inclined to a feed direction which is the direction of travel of the tape leaving the
supply spool[. and]

wherein the tip includes guide means on either side of the edge which operate in
conjunction with the shape of the tip for twisting the tape so that the path of the tape around
the edge between the guide means is in a plane substantially perpendicular to said edge and
inclined to the feed direction.

2. (amended) A correction tape dispenser comprising:
a tape comprising a carrier ribbon with correction composition thereon;
supply and take-up spools for the tape; and,
a tip having an edge for pressing the tape against a surface, a portion of the tape
between the supply and take-up spools being guided to extend around said edge, wherein the
edge is inclined to a feed direction which is the direction of travel of the tape leaving the
supply spool;

wherein the tip includes guide means on either side of the edge which operate in
conjunction with the shape of the tip for twisting the tape so that the path of the tape around
the edge between the guide means is in a plane substantially perpendicular to said edge and
inclined to the feed direction;

[A correction tape dispenser according to claim 1,] wherein the guide means on at least one side of the edge comprises a linear edge around which the tape passes from one side to the other side thereof.

3. (original) A correction tape dispenser according to claim 2, wherein the linear edges are provided on both sides and are defined by parallel ridges.

4. (previously presented) A correction tape dispenser comprising:
a tape comprising a carrier ribbon with correction composition thereon;
supply and take-up spools for the tape; and,
a tip having an edge for pressing the tape against a surface, a portion of the tape
between the supply and take-up spools being guided to extend around said edge, wherein the
edge is inclined to a feed direction which is the direction of travel of the tape leaving the
supply spool;

wherein the tip includes guide means on either side of the edge which operate in
conjunction with the shape of the tip for twisting the tape so that the path of the tape around
the edge between the guide means is in a plane substantially perpendicular to said edge and
inclined to the feed direction;

wherein the guide means on at least one side of the edge comprises a linear edge
around which the tape passes from one side to the other side thereof;

wherein the linear edges are provided on both sides and are defined by parallel ridges;
and

[A correction tape dispenser according to claim 3,] wherein the tape extends to the inner faces of the respective ridges from the supply and take-up spools, respectively.

5. (original) A correction tape dispenser according to claim 1, wherein tape positioning means are provided to determine a first fixed position from which the tape passes to the tip in the feed direction, and a second fixed position to which the tape passes after leaving the tip.

6. (previously presented) A correction tape dispenser according to claim 5 wherein the tip is provided by a unitary member and said tape positioning means are attached to said unitary [tip] member.

7. (original) A correction tape dispenser according to claim 1, wherein the guide means on at least one side of the tip comprises a guide element around which the tape passes to define a bend in the tape path.

8. (twice amended) A correction tape dispenser according to claim 7, wherein the guide element defines an arcuate surface contacted by the tape and the arcuate surface has an axis substantially perpendicular to a plane that contains [containing] the tip edge and that is parallel to the feed direction.

9. (original) A correction tape dispenser according to claim 1, wherein the guide means on at least one side of the tip comprises a guide element, the guide element twists the tape substantially through 90° between the feed direction and the tip edge.

10. (original) A correction tape dispenser according to claim 9, wherein guide elements are provided on both sides of the tip.

11. (amended) A correction tape dispenser according to claim 1, wherein the supply and take-up spools have rotational axes substantially perpendicular to a plane that contains [containing] the tip edge and that is parallel to the tape feed direction.

12. (amended) A correction tape dispenser according to claim 1, wherein the [tip] edge [direction] and the feed direction are at an angle in the range of about 45° to 75° to each other.

13. (original) A correction tape dispenser according to claim 1, wherein retaining means are provided adjacent at least one side of the tip edge for maintaining the tape in correct cooperation with said edge.

14. (original) A correction tape dispenser according to claim 13, wherein the retaining means comprises a pair of projections between which the tape passes.

15. (previously presented) A correction tape dispenser comprising:
a tape comprising a carrier ribbon with correction composition thereon;
supply and take-up spools for the tape; and,
a tip having an edge for pressing the tape against a surface, a portion of the tape
between the supply and take-up spools being guided to extend around said edge, wherein the
edge is inclined to a feed direction which is the direction of travel of the tape leaving the
supply spool;

wherein the tip includes guide means on either side of the edge which operate in
conjunction with the shape of the tip for twisting the tape so that the path of the tape around
the edge between the guide means is in a plane substantially perpendicular to said edge and
inclined to the feed direction;

wherein retaining means are provided adjacent at least one side of the tip edge for
maintaining the tape in correct cooperation with said edge;

wherein the retaining means comprises a pair of projections between which the tape
passes; and

[A correction tape dispenser according to claim 14,] wherein an element extends
between the projections to prevent the tape becoming disengaged therefrom.

16. (previously presented) A correction tape dispenser comprising:
a tape comprising a carrier ribbon with correction composition thereon;
supply and take-up spools for the tape; and,
a tip having an edge for pressing the tape against a surface, a portion of the tape
between the supply and take-up spools being guided to extend around said edge, wherein the
edge is inclined to a feed direction which is the direction of travel of the tape leaving the
supply spool;
wherein the tip includes guide means on either side of the edge which operate in
conjunction with the shape of the tip for twisting the tape so that the path of the tape around
the edge between the guide means is in a plane substantially perpendicular to said edge and
inclined to the feed direction;
wherein retaining means are provided adjacent at least one side of the tip edge for
maintaining the tape in correct cooperation with said edge; and

[A correction tape dispenser according to claim 13,] wherein the tape retaining means is arranged to define with the tip an eye through which the tape passes.

17. (original) A correction tape dispenser according to claim 16, wherein the retaining means comprises a pair of oppositely directed L-shaped projections, a slot being formed between the projections to allow the tape to be inserted through the eye.

18. (original) A correction tape dispenser according to claim 16, wherein the retaining means comprises a part surrounding the tip to form an eye on either side thereof.

19. (original) A correction tape dispenser according to claim 18, wherein said retaining part is a collar engaged with a push fit over the tip edge.

20. (original) A correction tape dispenser according to claim 1, wherein the tip edge is provided with extension portions to reduce the chances of the tape becoming displaced over an end extremity of the tip edge.

21. (original) A correction tape dispenser according to claim 1, further including a case enclosing the supply and take-up spools, the case being elongated substantially in the feed direction.

Claims 22-25. (canceled)

26. (new) A correction tape dispenser comprising:
a tape comprising a carrier ribbon with correction composition thereon;
supply and take-up spools for the tape; and,
a tip having an edge for pressing the tape against a surface, a portion of the tape
between the supply and take-up spools being guided to extend around said edge, wherein the
edge is inclined to a feed direction which is the direction of travel of the tape leaving the
supply spool;
wherein the tip includes guide means on either side of the edge which operate in
conjunction with the shape of the tip for twisting the tape so that the path of the tape from the
guide means toward the edge is in a direction substantially perpendicular to the edge and
around the edge between the guide means is in a plane substantially perpendicular to said
edge and inclined to the feed direction.